

VERSACAMM VP-300 30" ECO-SOLVENT" INKJET PRINTER/CUTTER VERSACAMM VP-540 54" ECO-SOLVENT" INKJET PRINTER/CUTTER













printing conditions. Media setup is easy as well with eight media presets for printing, cutting and heater temperature. VersaCAMM VPs also feature an automated cleaning system which allows immediate printing at any time, even if the machine has been idle for an extended period of time.

Powerful ECO-SOL MAX INK...vibrant, durable and safe

A remarkable innovation in ink technology, ECO-SOL MAX provides fast drying time, high density, wide color gamut, rugged scratch resistance, low cost per sqft, and broad uncoated media support. MAX is virtually odorless and graphics are water and UV resistant up to 3 years outdoors* without lamination. An integrated heating system helps ink bond to both uncoated and coated media and improves drying.

Advanced media handling for more efficient production

The VersaCAMM VP delivers superior media handling, allowing you to experience optimum performance on a wide variety of media options. Wide media flanges and seven pinch rollers secure the heaviest media in place for accurate feeding and tracking through even the longest production runs. Adjustable print heads enable you to accommodate variable media thicknesses.

To improve performance during unattended printing, an optional heavy-duty media take-up system accommodates rolls weighing up to 66 lbs (VP-540) or 44 lbs (VP-300).

Designed to be rugged and reliable

The VersaCAMM VP is a bulletproof workhorse that requires significantly less servicing than most inkjets to provide years of reliable service. It's backed with a two-year trouble-free warranty and our Passport Customer Care Program.

Includes VersaWorks™ RIP with Enhanced Productivity Tools

VersaWorks[™] adds powerful productivity tools to our robust software RIP with an easy-to-use interface that allows even novice users to take advantage of our printers' and printer/cutters' full potential.

Roland Color is a revolutionary spot color fidelity system that allows you to select the right color to match an established corporate or team color, or other vector graphic and then print that color with 100 percent accuracy every time. Variable Data Printing allows you to quickly and easily produce a series of digital prints in which text and graphics change from one print to the next. This feature is ideal for producing labels, name badges, plaques and menus.

VERSACAMM VP-540 54" PRINTER/CUTTER Roland

VERSACAMM VP-300 30" PRINTER/CUTTER

Shown with optional heavy-duty media take-up system.

Roland



VERSACAMM® VP ECO-SOLVENT® INKJET PRINTER/CUTTERS



PRODUCT HIGHLIGHTS

- Integrated print/cut capabilities
- Photorealistic CMYK printing up to 1440 dpi
- Variable Droplet Technology for superb detail
- Max. print speeds up to 166 sqft./hr. (VP-540) and 124 sqft./hr. (VP-300)
- 54" Maximum media width (VP-540) 30" Maximum media width (VP-300)
- Advanced ECO-SOL MAX INK
 - > Available in 440 or 220 cc cartridges
 - > Bonds to both uncoated and coated media
 - > Vibrant water, scratch and UV resistant graphics
 - > 3-year outdoor durability without lamination*
 - > No special ventilation equipment required
- Roland VersaWorks™ RIP software included > Roland Color System
 - > Variable Data Printing
- Automated Maintenance System
- Optional media take-up system supporting rolls up to 66 lbs (VP-540) and 44 lbs (VP-300)
- Two-Year Trouble-Free Warranty**

SPECIFICATIONS		VERSACAMM VP-300	VERSACAMM VP-540
Print resolution		540 x 360, 360 x 720, 720 x 720, 1080 x 1080, and 1440 x 720	
Printing/cutting width		6-3/16 to 29 in. (157 to 736 mm)	7-5/16 to 53 in. (185 to 1346 mm)
Acceptable media width		7-3/16 to 30 in. (182 to 762 mm)	8-5/16 to 54 in. (210 to 1371 mm)
Ink cartridges	Type Capacity Color	Roland ECO-SOL MAX INK 4 cartridges: 220 cc ±5 cc or 440 cc ±5 cc Cyan, Magenta, Yellow, Black	
Printing/cutting speed		Maximum 124 sq. ft./hr / 11.8 ips	Maximum 166 sq. ft./hr / 11.8 ips
Cutting force/offset		30 to 300 gf / 0 to 1.5 mm	
Interface		Ethernet (10 BASE-T / 100 BASE-TX, automatic switching)	
Power-saving function		Automatic sleep feature	
Power supply		Maximum: 5.8 A (AC 100 to 120 V ±10% 50/60 Hz)	Maximum: 8.3 A (AC 100 to 120 V \pm 10% 50/60 Hz)
Dimensions (with stand)		66.9 [W] x 39.4 [D] x 44.3 [H] in. (1699 [W] x 1000 [D] x 1125 [H] mm)	90.9 [W] x 39.4 [D] x 44.3 [H] in. (2308 [W] x 1000 [D] x 1125 [H] mm)
Weight (with stand)		193 lb (87.5 kg)	240 lb (109 kg)
Environment	Power on Power off	Temperature: 59-90°F (15-32°C) (68°F+ recommended) Humidity: 35-80% (no condensation) Temperature: 41-104°F (5-40°C) Humidity: 20-80% (no condensation)	

^{*} Outdoor durability is based on accelerated weather tests. Results may vary depending upon location and application. Dry times vary depending on specific media characteristics. Lamination may be required for some applications or environmental conditions. Specifications subject to change. **Continuous exclusive use of Roland Inks during the first two years of ownership is required to qualify for the free second year of limited warranty coverage. Additional Terms and Conditions apply.



