



HIGH PERFORMANCE

VINYL CUTTERS

BRING GRAPHICS TO LIFE

With plug-and-play ease, technological sophistication, compact convenience, and the reliability you expect from Roland, our full line of performance vinyl cutters accelerate your ability to create professional signs, displays, vehicle graphics, decorated apparel and window tinting. Each comes with all the hardware and software you need to get started immediately – right out of the box.



REV UP YOUR PROJECTS WITH PROFESSIONAL-QUALITY SOFTWARE TOOLS.

Roland cutters include Roland CutStudio™ software. CutStudio™ lets designers quickly and easily create graphics, position text on curves, enlarge, reduce, re-position, rotate and mirror images. Designs can be imported in BMP, JPG, STX, AI, and EPS file formats.



CutStudio™ includes a Windows XP/Vista printer driver, a plug-in for Adobe® Illustrator® 9/10/CS/CS2/CS3/CS4, a plug-in for CorelDRAW® 10/11/12/X3/X4, and a plug-in for Adobe Illustrator 9/10/CS/CS2/CS3/CS4 in the

Macintosh OS 9/X environment. Roland cutters also work with all popular sign making software for maximum flexibility.

Roland VersaWorks is powerful RIP software developed by Roland engineers for the company's inkjet technology and built upon the genuine Adobe® PostScript® CPSI™ RIP engine. For those customers who already own a Roland inkjet device, your VersaWorks RIP Software features an efficient graphical user interface that allows users to maximize their Roland inkjet through offline cutting without sacrificing print production.



OWNING A ROLAND



Your Roland ownership experience is our #1 priority and begins the moment you complete your purchase. Our Roland Care Passport is the industry's most extensive bundled service and support contract, giving you access to Roland warranties, on-site installation and training, e-mail and telephone technical support, user forums, newsletters and more. Roland also offers a variety of training courses through Roland University to help you build your business with important new skills.

PRODUCT SPECIFICATIONS

| MODEL | GX-300 | GX-400 | GX-500 | GX-24 |
|------------------------|--|---|--|---|
| Maximum cutting area | 29 x 984-1/8" (737 x 24,998 mm) | 39 x 984-1/8" (1000 x 24,998 mm) | 47 x 984-1/8" (1195 x 24,998 mm) | 2 to 27.5" (50 to 700 mm) |
| Acceptable media width | 2 to 36" (50 to 915 mm) | 3-1/2 to 46" (90 to 1178 mm) | 3-1/2 to 54" (90 to 1372 mm) | Width: 22.9" (584 mm) Length: 984" (25 mm) |
| Maximum cutting speed | 33 in/sec (850 mm/sec) [in all directions] | | | 4 to 20 in/sec (10 to 500 mm/sec) |
| Cutting force | 20 to 350 gf | | | 30 to 250 gf |
| Interface | Serial (RS-232C compatible), USB (Rev. 1.1) | | | USB interface (compliant with Universal Serial Bus Specifications Revision 1.1) |
| Power supply | AC 100 V to 240 V +/- 10% 50/60 Hz 1.2 A | AC 100 V to 240 V +/- 10% 50/60 Hz 1.1A | | Dedicated AC adapter; Input: AC 100 to 240 V +/- 10% 50/60 Hz 1.7 A Output: DC 24 V, 2.8 A |
| Dimensions | With stand 45-1/16 (W) x 28-5/8 (D) x 43-13/16" (H) 1144 (W) x 727 (D) x 1113 mm (H) | With stand 55-3/8 (W) x 28-5/8 (D) x 43-13/16" (H) 1407 (W) x 727 (D) x 1113 mm (H) | With stand 63-1/16 (W) x 28-5/8 (D) x 43-13/16" (H) 1602 (W) x 727 (D) x 1113 mm (H) | 33.5 (W) X 12.2 (D) X 9.25" (H) 851(W) X 310 (D) X 235 mm (H) |
| Weight | With stand 97 lb. (44 kg) | With stand 112.4 lb. (51 kg) | With stand 121.2 lb. (55 kg) | 35 lb. (16 kg) |
| Standard accessories | Power cord, blade, blade holder, alignment tool, cable clamp, replacement blade for separating knife, Roland Software Package CD-ROM, startup guide, user manual | | | AC adapter, power cord, blade, blade holder, separating knife, roller base, tweezers, test-use material, application tape, USB cable, "Roland Software Package CD-ROM," user's manual |
| Warranty | 3 years on the GX Pro (with registration) | | | 2 years on GX-24 (with registration) |

| MODEL | SV-15 | SV-12 | SV-8 |
|------------------------|--|---|--|
| Maximum cutting area | 13-3/8 (X) x 39-5/16" (Y) [340 (X) x 1000 mm (Y)] | 9-13/16 (X) x 39-5/16" (Y) [250 (X) x 1000 mm (Y)] | 6-1/4 (X) x 39-5/16" (Y) [160 (X) x 1000 mm (Y)] |
| Acceptable sheet width | Width: 14-1/8 to 15" (360 to 381 mm) Width: 11 to 12" (280 to 305 mm) Length: 43-1/4" (1100 mm) or less | Width: 11 to 12" (280 to 305 mm) Length: 43-1/4" (1100 mm) or less | Width: 7-13/16 to 8-7/16" (200 to 215 mm) Length: 43-1/4" (1100 mm) or less |
| Maximum cutting speed | 7/16 to 3-7/8 in/sec (12 to 100 mm/sec) | 7/16 to 1-9/16 in/sec (12 to 40 mm/sec) | 7/16 to 1-9/16 in/sec (12 to 40 mm/sec) |
| Interface | USB 1.1 | | |
| Power supply | Dedicated AC adapter input: AC 100 V +/- 10%, 50/60 Hz 1.7 A Output: DC 19 V 2.1 A | | |
| Dimensions (external) | 20-5/8 (W) x 8-1/8 (D) x 4-1/2" (H) 522 (W) x 205 (D) x 115 mm (H) | 17-3/8 (W) x 8-1/8 (D) x 4-1/2" (H) 440 (W) x 205 (D) x 115 mm (H) | 13-3/8 (W) x 8-1/8 (D) x 4-1/2" (H) 340 (W) x 205 (D) x 115 mm (H) |
| Weight | 7.3 lb. (3.3 kg) | 6 lb. (2.7 kg) | 4.9 lb. (2.2 kg) |
| Standard accessories | AC adapter, power cord, USB cable, replaceable blade protector, blade, blade holder, pin, material for test cuts, application tape for test cuts, Roland Software Package CD-ROM, SV-15/12/8 user's manual | | |
| Warranty | 1 year | | |

Imagine. Roland®

FOR COMPLETE PRODUCT SPECIFICATIONS AND FEATURES, OR MORE INFORMATION, CALL 800-542-2307 OR VISIT WWW.ROLANDDGA.COM
 ROLAND DGA CORP. | 15363 BARRANCA PARKWAY | IRVINE, CALIFORNIA 92618-2216 | 800.542.2307 | 949.727.2100 | CERTIFIED ISO 9001:2008
 RDGA-Cutters-01 September 2009